



D2262-041 SHORT ARM ASSY

D2262-1 SHORT ARM



14.03.12

С

NOTES

1) MATERIAL: D2262-1: AISI 304/316 SS SEAMLESS ROUND TUBING PER ASTM A213 OR ASME SA213 OR ASTM A269

1/2" OD X 0.035" WALL (REF DART SPEC M304TR0.500W.035)
2) FINISH: D2262-1: POWDER COAT "BLACK SANDTEX" (4.3.5.7) PER DART QSI 005 4.3
D2262-041: NONE

3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED

4) UNITS: INCHES UNLESS OTHERWISE NOTED

5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX 6) IDENTIFICATION: IDENTIFY ASSEMBLY WITH DART P/N "D2262-041" USING A REMOVABLE TAG PER DART QSI 044 6.6

7) WEIGHT: 0.07 lbs

8

8) ASSEMBLE D5077-1 SPACERS (QTY 2), D2262-1 SHORT ARM AND A1449 GROMMET AS SHOWN AND SWAGE GROMMET.

APPROVED	Α	NEW ISSU	VISSUE			94.08.10
	REV.		[DESCRIPTION	BY	DATE
	DESIGN		MC	DART AEROSPACE LTD		
	DRAWN		DB	HAWKESBURY, ONTARIO, CANADA		
	CHECKED		AP	DRAWING NO.		REV. B
	MFG. APPR.		JLM	D2262		SHEET 1 OF 1
	APPROVED		MP "/	TITLE		SCALE
	DE APPR.		DS	SHORT ARM ASSY		NTS
	DATE 14.03.12			COPYRIGHT © 1994 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		

RE-FORMAT DRAWING, ADD HOLE-TO-HOLE DIMENSION

7 6 5 4 3